

CWT 1736 CLASSIC

PREMIUM FLATBED APPLICATOR TABLE

KEY INFO

- Electronic table height adjusts 750 to 1,100mm to reduce operator fatigue.
- Massive safety glass bed features a built-in self-healing cutting mat.
- Handles an array of rigid substrates up to a thickness of 70mm easily.
- Rolling material holders provided for both the bed end and glide beam.
- Optional integrated LED illuminated worktable enables precision cutting.
- Flat-packed delivery simplifies on-site installation in tight spaces.

OVERVIEW

The CWT 1736 Advantage is a flatbed applicator built for steady, everyday sign production. It features a 4,000mm (13ft. 1in.) table with a 3,550 × 1,650mm (11ft. 7in. × 5ft. 5in.) working surface, electronic height adjustment, and a safety glass bed with self-healing cutting mat. Flat-packed for easy on-site installation, it is positioned at a low to mid-range price point and is used by sign makers, digital print centers, car wrappers, and road sign manufacturers.

SPECIAL FEATURES

The CWT 1736 CLASSIC features electronic work height adjustment between 750-1,100mm, allowing operators to set the table to their preference and reduce fatigue. Roll holders are included for both the bed end and glide beam. An optional LED illuminated work surface is available for precision cutting and alignment. The unit handles substrates up to 70mm thick and ships flat-packed for straightforward installation.

APPLICATIONS

The CWT 1736 CLASSIC handles laminating, mounting, premasking, and specialty signage production. This includes applying overlaminates to large format prints, adhering self-adhesive vinyl to rigid substrates like coroplast, gatorboard, acrylic, and aluminum, applying premask tape to cut vinyl graphics, and assembling multi-material panels, car wrap vinyl, and traffic signs.



SALES CHANNEL RESELLER

MADE IN SWEDEN

WARRANTY 3-YEAR

FACTS & SPECS

Table Length	3640 mm (11 ft 3 in)
Table Width	1720 mm (5 ft 8 in)
Working Area	3200 mm (10 ft 6 in)
Overall Width	2045 mm (6 ft 9 in)
W.A. Width / Roller	1650 mm (5 ft 5 in)
Max Substrate	0–70 mm (0–2.7 in)
Work Height	2ft 6in-3ft 7in
Bed Surface	Safety Glass with Mat
Power	120V 60Hz / 230V 50Hz
Air Supply	87-116 psi / 6-8 bar
Net Wt.	1124 lbs / 510 kg
Gross Wt.	1466 lbs / 665 kg
Pkg Dims	13ft 6in x 1ft 10in x 6ft 11in / 4120x560x2100mm

SPECIAL REQUIREMENTS

Requires 230V/50Hz (10A) or 120V/60Hz (15A) power and 6-8 bar compressed air. At 510 kg net weight, coordinate lifting equipment. Ships flat-packed in a single parcel.

FOR ADDED INFORMATION

USA: CUTWORX USA
Web: www.cutworxusa.com

HQ: CWT Worktools AB
Address: Arstidsvägen 8, 665 35
KilKarlstad, Sweden
Web: www.cwtworktools.com
Telephone: +46 554 333 90