

ROLLOVER CLASSIC F3315

FLATBED APPLICATOR WORKTABLE

KEY INFO

- Single-piece float glass bed ensures seamless full-surface lamination.
- Features a 175W LED illuminated glass bed with a self-healing cutting mat.
- Absence of an overhead gantry keeps the main work surface entirely clear.
- Caster-mounted design allows for easy relocation with no leveling required.
- Single-button operation is accessible from both table sides.
- Effortlessly handles a variety of thick substrates up to 78mm deep.

OVERVIEW

Designed and engineered in Norway, the Rollover Flatbed Applicator has been solving sign shop production challenges since its European launch in 2011 and US introduction in 2013. Headquartered in Mysen, Norway, Rollover AS now serves customers in more than 60 countries. The line includes the ROLLOVER CLASSIC F3315, which maintains the unobstructed roller access and high build quality that this global brand is known for across the industry.

SPECIAL FEATURES

The ROLLOVER CLASSIC F3315 offers an 11ft by 5ft 1in glass bed with a 175W LED illuminated surface and 13cm roller diameter. The single-piece float glass bed accommodates full-surface lamination without seam interference, and the roller handles substrates up to 78mm thick. Like all units, it operates from both sides with single-button control, ships on casters, and requires no leveling, making it suited for high-volume sign shops handling oversized media.

APPLICATIONS

The ROLLOVER CLASSIC F3315 is suited for large-format self-adhesive vinyl application, transfer film mounting, wide format lamination, road sign and traffic graphics production, banner finishing, and glass graphics preparation. Its working surface accommodates oversized panels and media that smaller flatbed applicators cannot handle, while the 175W illuminated glass bed supports precision cutting and alignment on large substrates up to 3.07 inches thick.



SALES CHANNEL RESELLERS

MADE IN NORWAY

WARRANTY 5-YEAR

FACTS & SPECS

Glass Bed Area	11ft x 5ft 1in /
Roller Bed Area	10ft x 5ft 1in /
Roller Diameter	5.1in / 13cm
Max Substrate	2.5in / 65mm
Work Height	35.4in / 900mm
Approx. Wt.	990 lbs / 450 kg
LED Illum.	175W
Power Supply	120V 60Hz / 230V 50Hz

SPECIAL REQUIREMENTS

Requires 230V/50Hz or 120V/60Hz power, a floor rated for 990 lbs, lifting equipment, and compressed air. The unit disassembles into three sections to navigate tight access points.

FOR ADDED INFORMATION

USA:
Web: www.rollover.no

HQ: Rollover AS
Address: Ramstadløkka 3 1850,
Mysen NORWAY
Web: www.rollover.no
Telephone: +47 69 89 8888