PRINTERS

CRIO 8432WDT

DESKTOP WHITE TONER (POWDERLESS DTF+) TRANSFER PRINTER

crio

SALES CHANNEL RESELLER

WARRANTY 1-YR/2-YR ONSITE*

*Based on Package Purchased

KEY INFO

- Desktop white toner printer transfers designs onto nearly any material.
- Prints CMYK or white in a single pass with swappable toner stations here.
- Self-weeding process needs no cutting, weeding, or background removal.
- Straight paper path resists jams across a wide range of transfer media.
- Ships with CADlink Digital Factory RIP software ready to print out.

OVERVIEW

The Crio 8432WDT White Toner Transfer Printer is a compact 4-color, 4-station desktop system that transfers single or multi-color designs onto paper, film, and transfer sheets up to 11" wide and 52" long. Its Powderless DTF+ process prints CMYK or white in a single pass, with no minimum order quantity, so shops can profit from a run of one sheet or a hundred at roughly $0.35 per sheet in toner cost.

SPECIAL FEATURES

The Crio 8432WDT combines a multilevel LED printhead with microfine toner for sharp detail at up to 1200 x 600 dpi, and its straight paper path avoids the jam points common on comparable printers. Swappable black and white toner stations print onto light or dark materials from the same machine, and the self-weeding process eliminates cutting, weeding, and background removal from the workflow entirely.

WORKFLOW & SUPPORT

The 8432WDT ships ready to print with CADlink Digital Factory RIP software included, plus access to the MyCrio Support portal for instructional videos and free training. Crio Support backs the printer with a 1-2 year onsite warranty.

FACTS & SPECS

Speed (8.5x11)	**16 ppm**
Speed (11x17)	**9 ppm**
Processor	**800MHz PowerPC**
Resolution	**1200x600 dpi**
Memory	**256MB**
OS Compatibility	**Win10+ / Mac10.10+**
Network Interface	**10/100/1000 Enet**
Local Port	**USB 2.0**
Scalable Fonts	**80 PostScript**
Media Capacity	**400 sheets max**
Max Media Size	**11.6 x 52 in**
Unit Size	**17.6x21.7x14.2in**
Weight	**81.7 lb (37kg)**
Power (Active)	**700W max/1400W**
Power (Standby)	**100W**
Noise (Active)	**52dBA or less**
Temp/Humidity	**50-90F/20-80%RH**

SPECIAL REQUIREMENTS

The Crio 8432WDT draws up to 700W active (1,400W peak) and 100W on standby, and runs best between 50°F-90°F at 20%-80% humidity, with a tighter 66°F-80°F, 50%-70% quality-assured range recommended.

It requires a Windows 10 or Mac 10.10 or later computer running CADlink Digital Factory, connected via Ethernet or USB 2.0.

FOR ADDED INFORMATION

HQ: CRIO

Address: 15720 Westport Commerce Drive
St. Louis, MO 63416
Telephone: +1.800.562.7760
Web: www.goisw.com