

PRINTERS

POLYPRINT FILMJET MINI DTF

ALL-IN-ONE DTF PRINTING SYSTEM

KEY INFO

- All-in-one system: printer, powder application, and curing in one chassis
- Touchscreen UI with guided maintenance keeps every operator on track daily
- Wireless file transfer sent straight from a smartphone over WiFi network
- Dual Epson i1600 or i3200 print heads, upgradeable for more productivity
- One year warranty including print heads, with full factory calibration
- Active wet-capping and white ink agitation prevent clogs during holidays

OVERVIEW

The Filmjet Mini DTF Printer Series is an all-in-one DTF system that combines printing, powder application, and curing in one compact chassis. A built-in Mini PC, pre-installed RIP software, and integrated air purifier remove the need for separate units, while dual Epson i1600 or i3200 print heads deliver vibrant color and strong white on garments from a footprint that fits into tight shops.

SPECIAL FEATURES

The Filmjet Mini DTF Printer Series accepts files over USB, network, or direct WiFi transfer from a smartphone, and its touchscreen UI guides operators through daily checks so the system stays healthy across shifts. Active wet-capping and white ink agitation prevent clogs during downtime, while ink-level, film-end, and powder-end sensors plus an anti-crash print head carriage keep production safe and unattended-ready.

APPLICATIONS

The Filmjet Mini DTF Printer Series suits shops starting DTF production or replacing separate print, powder, and cure units with one compact system, from small studios needing the 13-inch Mini 30 to higher-volume shops running the 24-inch Mini 60. Its stable ink delivery and precision print heads suit color-critical apparel work, photographic artwork, and dark-garment transfers that depend on dense, opaque white.



polyprint
DTF PRINTERS

SALES CHANNEL RESELLER

WARRANTY 1-YR

FACTS & SPECS

System Set-Up	All-in-One DTF System
P. Heads	2x i1600/i3200, guard, wet cap
Ink Supply	Bulk 500ml. CMYK, Lt. White
Max Print W. Mini 30 (15in)/Mini 60 (24in)	
Ink Type	Pigment Ink
Certification	OEKO-TEX
White Ink	Auto Recirculate
Connectivity	Ethernet, USB
Op. Conditions	20-25°C, 50-60% RH
Op. System	Integrated Mini PC
RIP Software	Built-in; 3rd-party opt.
Assembly	EU assembly, calib. & QC by Polyprint

**For additional info go to website*

SPECIAL REQUIREMENTS

The Filmjet Mini requires 230V, 50–60Hz power — 16A (3.7kW max) on the Mini 30, or 25A (5.2kW max) on the Mini 60 — and runs best at 20–25°C with 50–60% relative humidity.

The integrated Mini PC and RIP software need no external computer, and the built-in air purifier requires no separate ventilation setup.

FOR ADDED INFORMATION

HQ: Polyprint S.A.

**Address: 7th km Simmachiki str. - Oreokastrou
57013 Thessaloniki, Greece
Telephone: +30.2310.545087
Email: info@polyprintdtg.com
Web: polyprintdtf.com**